

CHAPTER 141

STREET CUTS AND STANDARDS

141.01 Street Cuts

141.02 Fees and Standards

141.03 Fines

141.01 STREET CUTS. No person shall cut cement of a street curb or the street itself unless authorized by the Council. All street and curb cement cutting shall be done by the City employees or by a contractor that is approved by the City.

141.02 FEES AND STANDARDS. The following fees and standards apply to any street cutting which is done within the City limits:

1. Brick Streets.
 - A. A fee of \$50.00 will be charged if only half the width of the street is sawed. A fee of \$100.00 will be charged if the whole width of the street is sawed.
 - B. If work being done is to be parallel with the street, sawing is required. If material being excavated is of clay, mass of dirt or frozen material, it will be hauled away and fill sand will be used to backfill. One foot compacted lifts will be brought to within 12" of the street surface, then 6" of $\frac{3}{4}$ " road stone or 1" of clean rock and a minimum of 6" of concrete.
2. Seal-coated Streets.
 - A. A fee of \$75.00 will be charged if only half the width of the street is sawed. A fee of \$150.00 will be charged if the whole width of the street is sawed. A fee of \$50.00 will be charged if only half the width of the street is sawed and the street has not been resealed. A fee of \$100.00 will be charged if the whole width of the street is sawed and the street has not been resealed.
 - B. If material being excavated is of clay, mass of dirt or frozen material, it will be hauled away and fill sand will be used to backfill. One foot compacted lifts will be brought to within 12" of the street surface, then 6" of $\frac{3}{4}$ " road stone or 1" of clean rock. Then 6" of cold mix will be added to be flush with the existing street surface.

3. Asphalt Streets.
 - A. A fee of \$100.00 will be charged if only half the width of the street is sawed. A fee of \$200.00 will be charged if the whole width of the street is sawed.
 - B. If material being excavated is of clay, mass of dirt or frozen material, it will be hauled away and fill sand will be used to backfill. One foot compacted lifts will be brought to within 12" of the street surface, then 6" of $\frac{3}{4}$ " road stone or 1" of clean rock. Then 6" of asphalt or 6" of concrete will be brought to the existing street surface.
4. Concrete Streets.
 - A. A fee of \$150.00 will be charged if only half the width of the street is sawed. A fee of \$300.00 will be charged if the whole width of the street is sawed.
 - B. If the saw cut is within half of the panel from the original joint, only that half will be replaced. If the cut is in the center of the panel, the whole panel will be replaced.
 - C. If material being excavated is of clay, mass of dirt or frozen material, it will be hauled away and fill sand will be used to backfill. One foot compacted lifts will be brought to within 8" below the bottom of the existing concrete, then 6" of $\frac{3}{4}$ " road stone or 1" of clean rock. The concrete being poured back into the street will be a minimum of 2" thicker than the original thickness. A $\frac{3}{4}$ " dowel will be used in the patch at width of 18" apart. Sixteen inch dowels will be used with half of the dowel being drilled into the existing slab. Dowels will be located halfway between the top and bottom of the patch being poured with a broom finish.
5. Curbs.
 - A. The fee for cutting of a curb shall be five dollars per foot.
 - B. The City shall only cut the curb. No removal of the sawed curb shall be done by the City. The saw cut will be within 6" of the water flow in curb lines. The curb that is to be cut for sewer or water repairs may have this fee added on the street cutting fee.
6. Driveways.

- A. Driveways that will be poured to concrete streets shall have rubber sealant poured into the saw cut.
- B. New driveways shall have a minimum of 6" of concrete. Sidewalks through the driveway will be of the same depth, if all are within the City right-of-way.
- C. Single drive shall be 18 feet at the street. Double drive shall be 24 feet at the street. Footage includes a branch out at the street. Variances shall be granted at the discretion of the Public Works Director.
- D. Concrete driveways being constructed on non-concrete streets shall be at least 18" from the edge of the existing street. Cold mix or rock may then be used to meet with the existing street.

141.03 FINES. Violations of this chapter shall result in fines of \$100 as well as restitution to the City for any costs or damages incurred.

o o o o o o o o o o